

X MULTI

Short and long distances on all types of roads

#MICHELINXMULTI

MICHELIN X[®] MULTI™ **WINTER T**

SAFETY AND MOBILITY IN WINTER, DOWN TO THE LAST KILOMETRE

TRAILER AXLES



385/65 R 22.5

M+S MARKING AND 3 PMSF







GRIP AND TRACTION IN SNOW AND ICY ROAD CONDITIONS

THROUGHOUT THE ENTIRE LIFE OF THE TYRE







" Maximise profitability from your tyres "

- · Excellent mileage performance
 - Same mileage performance as the Michelin 385/65 R 22.5 XTE 3 tyre (internal Michelin test conducted in 2013)
 - · Innovative and progressive siping
 - New CARBION™ material™
 - Large shoulders for improved resistance to lateral scrup
- Carcass is highly resistant to sidewall damage
 - Stronger casing ply than the Michelin 385/65R 22.5 XTE 3 (7% more metal threads)



"Grip in winter conditions up until the last kilometre"

- Excellent grip on wet, icy and snowy surfaces
 - Wet Grip A label
 - 3MPSF marking
- Grip maintained throughout the entire life of the tyre
 - Full-depth sipes




"Cleaner transport"

- Retreading and regrooving save materials and fuel
- Tyres manufactured in compliance with ISO 14001 environmental standards

INNOVATIVE AND PROGRESSIVE SIPING

Provides grip throughout the entire life of the tyre whilst limiting tearing and accidental damage **MICHELIN Durable Technologies**



• Three central ribs have large number of sipes.

- Two double-wave sipes on the tread blocks.
- A double-well sipe between each tread block.



Mid-wear tread

 The double-wave sipes gradually narrow down with wear to protect the tread against tearing, then exposed double-well sipes maintain grip

CARBION™

This innovative material significantly improves mileage potential owing to its resistance to abrasion MICHELIN Durable Technologies

MICHELIN X® MULTI™ WINTER T

Theoretical regrooving depth	Regrooving width	Blade	
H = 3 mm	8 - 10 mm	R3	



Regrooving diagram

TECHNICAL CHARACTERISTICS

						EUROPEAN LABELLING		
Tread and dimension	Airtightness	Load/speed index	Unique point index	Recommended Michelin rim	Special markings			((+))
385/65 R 22.5	TL	160 K	158 L	11.75 x 22.5	M+S, 3PMSF	С	А	((- 0)) 70 dB

Optional text 01 – delete if not needed

form more informations go on www.trucks.michelin.eu and You Tube www.youtube.com/michelintrucktyres Optional text 02 – delete if not needed

Optional text 03 – delete if not needed

