



**X<sup>®</sup> MULTI<sup>™</sup> F**

DESIGNED FOR NATIONAL AND REGIONAL OPERATIONS ON ALL TYPES OF ROAD

**MICHELIN**  
**X<sup>®</sup> MULTI<sup>™</sup> F**

**STEER AXLE**



**385/55 R 22.5**

**M+S MARKING**  
**3PMSF MARKING**



RADIO FREQUENCY IDENTIFICATION  
CHIP INTEGRATED



**CUT OPERATING COSTS**

**20% INCREASED MILEAGE POTENTIAL\***

**IMPROVED LONGEVITY\* AND MOBILITY  
IN ALL CLIMATIC CONDITIONS**



**MICHELIN**

*A better way forward*

\* Internal test (2015): tractor unit fitted with 385/55 R 22.5 MICHELIN X<sup>®</sup> MULTI<sup>™</sup> F compared with tractor unit fitted with 385/55 R 22.5 MICHELIN XFA2 ENERGY<sup>™</sup> AS



# MICHELIN X® MULTI™ F



## BUSINESS EFFICIENCY

REDUCE YOUR OPERATING COSTS

- 20% increased mileage potential\*
- Lower cost per mile\*
- Suitable for all road surfaces
- Low rolling resistance - European labelling B

\* Internal test (2015): tractor unit fitted with MICHELIN 385/55 R 22.5 X® MULTI™ F compared with tractor unit fitted with MICHELIN 385/55 R 22.5 XFA2 ENERGY™ AS

- A new generation of tread rubber mix that enables a reduction in original tread depth without affecting mileage performance.
- Larger tread width (+6 mm vs MICHELIN 385/55 R22.5 XFA2 ENERGY™ AS) that enables an optimised contact patch and slows down the wear rate.
- Delta sipes are aligned with the initial suggested direction of rotation for an improved wear pattern.



## SAFETY

SAFE TRANSPORTATION WHATEVER THE WEATHER CONDITION


- High level of grip
- M+S and 3PMSF markings
- New generation of blend of rubber mix.
- Delta sipes: the sipes are deep for optimal and lasting grip in winter conditions and slippery road surfaces.



## ECOLOGY

A GREENER WAY TO TRANSPORT GOODS

- Retreading and regrooving save materials and fuel
- Tyres manufactured in compliance with ISO14001 environmental standards
- Robustness of MICHELIN casing.



## Delta Sipe

Braking distance reduced and improved grip\* when cornering on slippery road surfaces.

## TECHNICAL INFORMATION

TREAD PATTERN AND DIMENSION	TYPE	LOAD/SPEED INDEX	ORIGINAL TREAD DEPTH	SPECIAL MARKINGS	MICHELIN PREFERRED RIM	EUROPEAN LABELLING		
385/55 R 22.5 MICHELIN X® MULTI™ F	TL	160K/158L	12mm	3PMSF, M+S	11.75			

## MICHELIN 385/55 R 22.5 X® MULTI™ F

THEORETICAL REGROOVING DEPTH	APPROXIMATE REGROOVING WIDTH	SUGGESTED BLADE
3 mm	8 - 10 mm	R3

## REGROOVING PATTERN



Regroovable and retreadable **MICHELIN** **Remix** on trailer axle.

MICHELIN products are manufactured from high quality materials to high tolerances, ensuring a uniform and consistent performance. Correct application, fitting, inflation and regular inspection of the product are essential to its safe and efficient operation. Remix and the tyre designations mentioned are trademarks of MICHELIN. For further information about any of the products in this document, contact your local MICHELIN representative or Technical Liaison helpline on 0845 366 1535.

### FOR MORE INFORMATION:



**INTERNET**  
trucks.michelin.co.uk



**MYACCOUNT**  
myaccount.michelin.eu

### CONNECT:



**SEE THE TESTIMONIALS AT**  
www.youtube.com/michelintrucktyres



**LINKEDIN**  
Michelin Trucks and Bus tyres Europe



**INSTAGRAM**  
@michelintruck



**FOLLOW US**  
@MichelinTruckUK

### CONTACT US:



**BY TELEPHONE**  
0845 366 1535

